Laquaforce®
WATER TREATMENT TECHNOLOGY

Product Specifications Datasheet

Chemical High Resistance Multi-cartridge Filter Housing

- **PVC-U multicartridges filter housings for 9 cartridges flanged top opening;**
- **with three pieces in / out female socket weld connections;**
- **with two ¼" threaded connections for air valve pressure gauges and for drain filter;**
- **all filter housing internal material and all internal spare parts are in PVC-U for high chemical corrosion resistance;**
- **opening gasket in silicone material;**
- **connection gasket in EPDM material;**
- **with aeration valve and pressure gauge;**
- **European 97/23/EC Directive compliant for pressure equipment (PED);**
- **design pressure = 6,0 bar;**
- **hydraulic test pressure = 7,8 bar;**
- **max Δp = 1,4 bar;**
- **operating temperature = 5 ÷ 40 °C;**
- **In/Out connections DN80 / D. 90 mm;**
- **½" drain connection;**
- **suitable for DOE cartridges;**
- **cartridges dimensions: ID 28÷30 mm, OD 65÷71 mm and length 20"- 30"- 40".**

REF.	CARTRIDGES NUMBER	WEIGHT (kg)	CAPACITY (litres)	Height	Diameter
FB564	9pc x 2,5" x 20"	20,0	39,7	745	395
FB565	9pc x 2,5" x 30"	23,0	57,0	995	395
FB566	9pc x 2,5" x 40"	26,0	74,3	1245	395

© A.P. Laquaforce Services Ltd

A.P.Laquaforce Services Ltd
www.laquaforce.com – info@laquaforce.com
4 Egnatias street, Kolossi, Lemesos
T: 7777 2782 – F:357 25755540

PROUD MEMBER OF:
IWA International Water Association

Currently under procedure of Accreditation ISO 9001